## Bluetooth® Sound Meter



## Wirelessly display, log, and transfer readings

Sper Scientific's Bluetooth® Sound Meter is small, light, and simple to use with results clearly displayed on the meter's large 1-1/2" backlit display. Choose A or C decibel frequency weighting scales and manual or auto ranging. Indicates readings over or under range and features minimum and maximum hold (peak) and data hold functions. The meter offers the convenience of Bluetooth® for wireless communication with free iOS app and coming soon to Android smart phone. Results can also be remotely viewed on your smartphone in real time, saved and exported. This enables the meter to be used as a remote wireless probe and as a datalogger. Comes ready to use with a windscreen, tripod screw, instructions and a 9V battery. N.I.S.T. traceable certificate of calibration available.



new	

No.	Description				
850019 850019C	Bluetooth® Sound Meter Bluetooth® Sound Meter Certified				
840093	Field Tripod				













A1 * : × ✓ fx FileName								
4	А	В	С	D	E	F	G	
1	FileName	Unit	Max	Min	Avg	Note		
2	7/7/2020 12:15	dBA	59	45.2	50.7286			
3		50	50	50				
4								
5	Sample	Date	Time	Unit(dBA)	Unit()	Unit()	Unit()	
6	1	7/7/2020	12:15:30	55.4	50-100			
7	2	7/7/2020	12:15:31	48.3	50-100			
8	3	7/7/2020	12:15:32	46	50-100			
9	4	7/7/2020	12:15:33	45.2	50-100			
10	5	7/7/2020	12:15:34	45.5	50-100			
11	6	7/7/2020	12:15:35	59	50-100			
12	7	7/7/2020	12:15:36	55.7	50-100			

**Dimensions** 

Weight

6.5 oz (184 g)

020	12:15:33	45.2	50-100				
020	12:15:34	45.5	50-100				
020	12:15:35	59	50-100				
020	12:15:36	55.7	50-100				
Range				Resolution	Accuracy		
35 to 130 dB				0.1 dB	±1.5 dB @ 94 dB, 1kHz		
7 ¼" x 2" x 1 ½" (185 x 54 x 36 mm)							